

## Interior (Drywall) Deflection Track Systems



Deflection products and systems are used in wall assemblies that are subjected to deflection including seismic disturbances, foundation settling, and normal head-of-wall compression. Deflection products allow for vertical movement while maintaining wall integrity and fire protection.

A variety of deflection products can be used including:

- **SLP-TRK\* Slotted Track**
- **Long Leg (Deflection) Track with Spazzer® Bridging Bar**
- **Long Leg (Deflection) Track with U-Channel and EasyClip™ Connectors (U-Series™)**
- **Double Track™ (Overtrack) System**
- **Fast Top™ Clip with Long Leg (Deflection) Track**

### SLP-TRK\* Slotted Track

- Positive attachment that allows up to 1" of vertical movement
- Meets ASTM, UL2079, IBC Building Codes
- UL\*\* Approved 1- and 2-hour systems
- Single track assembly



SLP-TRK®

A special benefit of the SLP-TRK® slotted track is that it attaches directly to the under side of roof decks or floor/ceiling assemblies, eliminating the need for special cutting or ship laps. Firestop caulking or spray applied fireproofing is required to achieve fire-rated performance.



U.S. Patent # RE 39,462

\*SLP-TRK is a registered trademark of SlipTrack Systems, Inc.  
 \*\* UL™ and UL Classified are trademarks of Underwriter's Laboratories, Inc.

### Long Leg (Deflection) Track with Spazzer® Bridging Bar

- Eliminates high material cost of custom-made head tracks
- Requires only a single generic Long Leg Track to accommodate deflection
- Facilitates sprayable intumescent/elastomeric firestops
- Eliminates stud spacing layout at deck
- Improves drywall hanging since bow is removed from tall studs
- Automatically positions and rigidly holds studs on 16" or 24" centers without fasteners in the head track



U.S. Patent No.  
5,784,850



### Long Leg (Deflection) Track with U-Channel and EasyClip™ Connectors (U-Series™)

- Nonproprietary system
- Traditional framing components
- Requires U-Channel and EasyClip™ Connectors (U-Series™)



### Double Track™ (Overtrack) System

- Eliminates bridging at the top row of knockouts
- Requires custom top track/longer lead times



### FastTop™ Connectors with Long Leg (Deflection) Track

- FastClip™ slip technology
- Available in 3" and 5" widths
- Attaches within the wall cavity
- Proprietary screws provide frictionless slip connections

