


Most cost-effective, positively attached fire-rated deflection system.



- Positive attachment that allows up to 1" of vertical movement
- Offers over 200 UL and ICC-ES Approved designs
- UL** Approved 1- and 2-hour systems
- Single track assembly



SLP-TRK®

It's a real challenge meeting head-of-wall codes for fire stop and life safety while maintaining the ability to absorb vertical movement in low-, mid- and high-rise buildings. SLP-TRK® slotted track is the solution.

SLP-TRK® slotted track provides a positive attachment for wall strength and allows for vertical movement. Movement caused by normal head-of-wall and floor extension or compression is absorbed by SLP-TRK® slotted track to prevent damage to the wall assembly.

SLP-TRK® slotted track systems comply with the toughest code requirements in North America, if not the world. It's been tested with a variety of leading fire-stop products and has outperformed the requirements of stringent fire and hose stream testing ASTM E 119 and ASTM E 814. SLP-TRK also has met and exceeded the latest seismic cycling standards found in UL2079 and ASTM E 1966.

Meeting Code Requirements

SLP-TRK® slotted track has achieved the following building code approvals:

- ICC-ES ESR 1042
- UL Classified R19236
- UL Certified for Canada XHL17
- LA City RR25344
- OSHPD R#0371
- NY City MEA 285-01-M
- National Building Code of Canada



SLP-TRK® Slotted Track (BDTK)

DMF Product Code	Thickness				Size***		Weight		Packaging	
	Gauge	Mils	Design Thickness		Inches	mm	lbs/ft	kg/m	Pcs/Bundle	Pcs/Skid
			Inches	mm						
BDTK	25	18	0.0188	0.478	2-1/2	63.5	0.484	0.718	N/A	112
					3-5/8	92.1	0.556	0.827		160
					4	101.6	0.580	0.859		144
					6	152.4	0.708	1.050		96
					8	203.2	0.836	1.240		80
BDTK	20	33	0.0346	0.879	2-1/2	63.5	0.882	1.309	112	
					3-5/8	92.1	1.015	1.505	160	
					4	101.6	1.059	1.571	144	
					6	152.4	1.294	1.922	96	
					8	203.2	1.529	2.270	80	
BDTK	18	43	0.0451	1.146	2-1/2	63.5	1.150	1.706	112	
					3-5/8	92.1	1.323	1.965	160	
					4	101.6	1.380	2.047	144	
					6	152.4	1.687	2.503	96	
					8	203.2	1.993	2.959	80	
BDTK	16	54	0.0566	1.438	2-1/2	63.5	1.443	2.142	112	
					3-5/8	92.1	1.660	2.463	160	
					4	101.6	1.732	2.571	144	
					6	152.4	2.117	3.142	96	
					8	203.2	2.502	3.713	80	
BDTK	14	68	0.0713	1.811	2-1/2	63.5	1.818	2.699	112	
					3-5/8	92.1	2.091	3.103	160	
					4	101.6	2.182	3.237	144	
					6	152.4	2.667	3.959	96	
					8	203.2	3.152	4.677	80	

*SLP-TRK is a registered trademark of SlipTrack Systems, Inc.

**UL and UL Classified are trademarks of Underwriters Laboratories, Inc.

***Custom sizes available upon request.