

Used to secure U-channel (cold rolled channel) to framing member for lateral bridging or to secure one framing member to another.

- 2" x 2" legs.
- Available in 3-3/8", 5-3/4", 7-3/4" and 9-3/4" lengths.
- Available in 16, 14 and 12 gauge.
- Prepunched for faster and more accurate fastener placement.
- G 90, 50 ksi steel.



EasyClip™ Support Clip (X-Series™)



Dietrich EasyClip™ X-Series™ support clips are used to secure U-channel to wall studs for lateral bridging. U-channel is passed through the stud knockout and an EasyClip™ X-Series™ clip is screw attached or welded to provide a rigid connection. Dietrich EasyClip™ X-Series™ support clips are also used to secure one framing member to another or to attach and reinforce headers and sills in door and window openings. X-Series™ clips are prepunched for faster and more accurate fastener placement.



EasyClip™ Support Clips (X-Series™)

EasyClip™ Support Clips (X-Series™)

DMF Product Code	Thickness				Size		Weight/Piece		Packaging
	Gauge	Mils	Design Thickness		Inches	mm	lbs	kg	Pcs/ Bucket
			Inches	mm					
X543	16	54	0.0566	1.438	2 x 2 x 3-3/8	50.8 x 50.8 x 85.7	0.194	0.088	200
X545	16	54	0.0566	1.438	2 x 2 x 5-3/4	50.8 x 50.8 x 146.0	0.324	0.146	170
X547	16	54	0.0566	1.438	2 x 2 x 7-3/4	50.8 x 50.8 x 196.8	0.453	0.205	100
X549	16	54	0.0566	1.438	2 x 2 x 9-3/4	50.8 x 50.8 x 247.6	0.583	0.264	100
X683	14	68	0.0713	1.811	2 x 2 x 3-3/8	50.8 x 50.8 x 85.7	0.245	0.111	200
X685	14	68	0.0713	1.811	2 x 2 x 5-3/4	50.8 x 50.8 x 146.0	0.408	0.185	100
X687	14	68	0.0713	1.811	2 x 2 x 7-3/4	50.8 x 50.8 x 196.8	0.571	0.258	100
X689	14	68	0.0713	1.811	2 x 2 x 9-3/4	50.8 x 50.8 x 247.6	0.734	0.332	80
X973	12	97	0.1017	2.583	2 x 2 x 3-3/8	50.8 x 50.8 x 85.7	0.349	0.158	100
X975	12	97	0.1017	2.583	2 x 2 x 5-3/4	50.8 x 50.8 x 146.0	0.582	0.263	100
X977	12	97	0.1017	2.583	2 x 2 x 7-3/4	50.8 x 50.8 x 196.8	0.814	0.369	60
X979	12	97	0.1017	2.583	2 x 2 x 9-3/4	50.8 x 50.8 x 247.6	1.047	0.474	60